



Alpha Design Labs Cruise Portable Headphone Amplifier

24/96 USB Input and Analog Line input • 3.5mm Headphone Output

Mirror-Polished Stainless-Steel Panel • Gorgeous Carbon Fiber Body • Elegant Appearance

Goes Anywhere • Rechargeable Battery • Superb Sound

Lust in High Places

It's the age of personal, portable electronics; everyone carries their music with them. Accessories reflect your personal style and the Cruise is sure to create jealousy and envy wherever you go. It delivers thrilling sound to match its gorgeous appearance. Whether you're using iTunes for low-bit-rate downloads or high resolution music files just connect your computer to the Cruise with one of our matching ADL Formula 2 USB cables or the new i-D35SP analog stereo cables. When you're on the road plug your music player's analog headphone output into the line input of the Cruise and open the player's volume to maximum and use the volume control on the Cruise. For higher resolution all-digital signals simply connect the Cruise to your computer's USB port. The USB port charges the battery and you can listen to music while it's charging!

Features

- Mega performance, Furutech takes what's there and makes it better!
- Beautifully finished, lustrous carbon fiber body and mirror-polish nonmagnetic stainless steel panel.
- Fits in the palm of your hand, enjoy your music anywhere
- High quality volume control (front) and On/Off switch (rear)
- Gold-plated 3.5mm analog line input (switched) or gold-plated USB digital input for PC audio (Phone jack overrides output from USB mini-B interface on rear panel)
- Runs on USB power or an AC/DC switching power adapter that recharges battery
- High performance headphone amplifier drives 12 to 600 ohm headphones
- Gold-plated circuitry on high quality printed circuit board

Front Controls and Indicators:

- a. HEADPHONES OUTPUT: 3.5mm phone jack
- b. LINE INPUT: 3.5mm switched phone jack
- c. VOLUME: Rotary type variable resistor
- d. One dual color RED and BLUE LED: BLUE indicates Power On / RED indicates Battery Low Voltage

Rear Panel:

- a. MASTER POWER ON/OFF
- b. USB: 1 USB mini-B Type
- c. Internal DC3.7V, 940mAh Li-ion Type 14650 Rechargeable Battery
- d. Charging Indicators: One dual-color RED and GREEN LED: RED indicates Charging / GREEN indicates Full Charge

Cruise Portable headphone amplifier Specifications

Output Jack: 3.5mm Phone Jack x 1	Headphone Output Level (Max.): 1%THD 1kHz
Input Jack: Line In (3.5mm switched Phone Jack) x 1, USB In (mini B type) x 1	78mW (12 ohm) 94mW (16 ohm) 110mW (32 ohm) 98.6mW (56 ohm) 23mW (300 ohm) 16mW (600 ohm)
Signal to Noise Ratio :	Frequency Response:
Line in: 100dB (A-Weighted)	Line in: 20Hz~20kHz (±0.5dB) headphone output
USB in: 96dB (A-Weighted)	USB in: 20Hz~20kHz (±0.5dB) headphone output
DAC Chip: WM8716 192kHz/24bit	Channel Separation: 60dB (1KHz)
USB Chip: TE7022L 96kHz/24bit	Total Harmonic Distortion: 0.02% (Line Input 1KHz)
Power Supply-1: DC5V , 2000mA , 10W Switching Power Adapter	Music Playback Time: Up to 80 hours when fully charged (5 hours charge time approx.)
Power Supply-2: DC3.7V, 940mAh Li-ion Type 14650 Rechargeable Battery	Dimensions: 65 (W) x 120 (D) x 28 (H) mm Weight: 198g Approx.

ADL product enquiries email: service@adl-av.com
Furutech Co., Ltd. Tokyo Japan
www.adl-av.com